

• TRUSTED QUALITY SINCE 1921 •

**RUST-OLEUM®**  
INDUSTRIAL CHOICE®

**M1600 SYSTEM  
PRECISION LINE® INVERTED MARKING PAINT**

## DESCRIPTION AND USES

Industrial Choice M1600 System Precision Line® is a general purpose inverted marking paint. Use for marking concrete, pavement, gravel, grass, and more. M1600 Precision Line is suitable for marking the location of underground utilities at construction and excavation sites where identification is desired.

## PRODUCTS

SKU	DESCRIPTION
1601838V	Clear
1634838V	Safety Green
1661838V	Fluorescent Pink
1662838V	Fluorescent Red
1669838V	Fluorescent Purple
1675838V	Black
201516V	APWA Orange
203022V	Caution Blue
203023V	Fluorescent Green
203024V	Caution Yellow
203025V	High Visibility Yellow
203026V	Alert Orange
203027V	Fluorescent Orange
203028V	Fluorescent Red-Orange
203029V	Safety Red
203030V	White
239007	Silver

## PACKAGING

Inverted 20 fl. oz. aerosol container, (17 oz. fill weight; except 239007 Silver: 16 oz. fill weight), 12 aerosols/carton.

## PRODUCT APPLICATION

### SURFACE PREPARATION

ALL SURFACES: Remove loose contaminants by sweeping the surface before application of the coating.

## PRODUCT APPLICATION (cont.)

### APPLICATION

Use when temperature is 40-90°F (10-32°C) and humidity is below 85% to ensure proper drying. This product can be used down to 25°F (-4°C) which may result in a slight reduction of delivery rate. Protect surrounding surfaces from overspray. Overspray can carry a significant distance. Shake can vigorously for one minute after mixing ball is heard. Invert can and point at ground or floor. Hold can 4 to 10 inches above surface to be marked. Press in sideways to spray or use Rust-Oleum Marking Wand (#2393000) or Rust-Oleum Marking Pistol (#210188). Follow directions for proper use of this equipment. Keep can moving to prevent build-up.

### CLEAN-UP

Clean valve by spraying upright for 2-3 seconds after each use. Properly discard empty container. Do not burn or place in trash compactor. Empty container can be recycled

### CLOGGING

If valve clogs, carefully remove spray tip and clean in thinner. **DO NOT** insert any object into can valve opening.

<b>AEROSOLS</b>	<b>TECHNICAL DATA</b>	<b>IC-52</b>
<small>• TRUSTED QUALITY SINCE 1921 •</small> <b>RUST-OLEUM®</b> <small>INDUSTRIAL CHOICE®</small>	<b>M1600 SYSTEM  PRECISION LINE® INVERTED MARKING PAINT</b>	

**PHYSICAL PROPERTIES**

	<b>PRECISION LINE INVERTED MARKING PAINT</b>
<b>Resin Type</b>	Hydrocarbon
<b>Pigment Type</b>	Varies with color
<b>MIR</b>	Maximum value of 0.85
<b>Fill Weight</b>	17 oz.; except 239007 Silver: 16 oz. fill weight
<b>Practical Coverage</b>	Approximately 600-700 linear feet at 1 inch wide
<b>Dry Times at 70-80°F (21-27°C) and 50% Relative Humidity</b>	Less than 1 hour
<b>Shelf Life</b>	5 years
<b>Safety Information</b>	For additional information, see SDS

Calculated values are shown and may vary slightly from the actual manufactured material.

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.