



KRYLON® FARM & IMPLEMENT™ ENAMEL QUART AND GALLON PAINTS

Heavy Duty Performance

PRODUCT DESCRIPTION	APPLICATION	CAUTIONS
<p>Krylon® Farm and Implement features Premium Weather guard technology for protection from corrosion and rust on metal, chemical resistance, fade resistance and can be applied directly to metal surfaces. For increased protection and hide when making drastic color changes, use Krylon® Farm and Implement Primer as base coat under paints.</p>	<p>Brush/Roll: Use a nylon/polyester or natural bristle brush or a natural or synthetic roller cover with solvent resistant core.</p> <p>Spray: If using a sprayer, follow all spray equipment manufacturer's instructions for safety, usage, grounding, ventilation and settings, ensuring proper ventilation and that all equipment is grounded. Do not use where static electricity could build up and ignite vapors. If electing to use a reducer, paint can be reduced up to 20% by volume with Krylon® 2045 Reducer, or, if regionally compliant, mineral spirits can be used to reduce paint up to 2% by volume. Reduction may impact film build and adhesion. Reducers will increase VOC of product. For best results, spray in several light mist coats. If desired, 1 half-pint of Krylon® 2046 Hardener additive can be added per each 1 gallon of paint. Krylon® Reducer and Krylon® Hardener can be used together for spray, brush and roller applications.</p> <p>Cleanup: Clean spills and overspray with a regionally compliant cleaning solvent, following solvent manufacturer's instructions. Recycle empty can and cap per local regulations. Contact Us: 1-800-247-3268 or ask@krylon.com. Satisfaction Guarantee: If dissatisfied, contact us with product number and batch code on product for full purchase price refund.</p>	<p>CONTENTS MAY CATCH FIRE. CONTENTS HARMFUL. MAY IRRITATE EYES. MAY IRRITATE SKIN. DANGER OF COMBUSTION.</p> <p>Do not smoke. Do not swallow. Do not get in eyes or on skin or clothing. Do not breathe fumes. Materials such as rags used with this product may begin to burn by themselves. After use, put rags in water or lay flat to dry, then discard. Use only in a well-ventilated area. Keep away from flames, such as pilot light, and any object that sparks, such as an electric motor. Keep out of reach of children. Wear gloves, goggles or respiratory protection.</p> <p>FIRST AID TREATMENT: Contains: alkyd polymer, light aliphatic hydrocarbon, methyl acetate, heavy aliphatic solvent. If swallowed, call a Poison Control Center or doctor immediately. Do not induce vomiting. If in eyes, rinse with water for 15 minutes. If on skin, rinse well with water. If on clothes, remove clothes. If breathed in, move person into fresh air.</p>
PAINTING CONDITIONS	CHARACTERISTICS	
<p>Apply outdoors or in a well-ventilated area. Protect surrounding areas. Best results when air and surface temperatures are between 55°F (12°C)-75°F (24°C) and humidity is below 60%. NOTE: Applying outside of this range may impact finish.</p>	<p>Colors: Available in 20 Colors</p> <p>Coverage: Estimated 100 Square Feet</p> <p>Drying Time, @ 77°F, 50% RH: <i>Drying time and recoat times are temperature, humidity, and film thickness dependent.</i></p> <p>Dry to Handle and Re-Coat – 24-48 hours</p> <p>Net Wt.: 32 oz. / 120 oz.</p> <p>Volume Solids: 55-65 %</p> <p>Weight Solids: 70-80 %</p>	
SURFACE PREPARATION		PERFORMANCE TESTING
<p>WARNING! If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead. Sand shiny surfaces. Surfaces should be clean, dull and dry. Remove loose rust and paint with wire brush or sandpaper.</p>		<p>Technical data furnished herein is accurate and true to the best of our knowledge. However, no guarantee of accuracy is expressed or implied. We assume no responsibility or liability as a result of purchase, coverage, application or injuries resulting in misuse. To contact us call 1-800-247-3268 or ask@krylon.com.</p>