



UPC Code: 07847722650 Country Of Origin: Mexico

# 5225

15 Amp, 120 Volt, Duplex Style Single-Pole / 5-15R AC Combination Switch, Commercial Grade, Grounding, Side Wired, - Brown

With Leviton's extensive assortment of combination devices, you can fill a one-gang space with two switches, a switch and receptacle, even a switch and GFCI. From sensor guide lights to multi-purpose styles and Tamper-Resistant receptacles, we accommodate your every need. These devices come in a range of colors and are backed by a limited two-year warranty. Built to last and designed to save space, these attractively styled devices are at home in any setting.

#### **Technical Information**

AC Horsepower Ratings HP Rating: 1/2HP-120V Max. Amperage: 12 Amp

Electrical Specifications Grounding: Grounding Receptacle Amperage: 15 Amp Receptacle Voltage: 125V AC Switch Amperage: 15 Amp

Switch Voltage: 120V AC Dielectric Voltage: Withstands 1500V for 1 minute

**Overload UL20 Test:** 100 cycles of OL at 4.8 times rated current

Temperature Rise: Maximum 30 degrees C rise

Environmental Specifications Flammability: Rated V-2 per UL 94 Operating Temperature: -40°C to 65°C

Material Specifications Actuator Material: Thermoplastic Body Material: Thermoplastic Strap Material: Steel

#### Features and Benefits

- AC quiet switches have silver-cadmium oxide contacts and receptacles have

double-wipe contacts for maximum conductivity

- All devices have grounding screw
- Side wired with terminal screws that accept up to #12 copper or copper-clad wire
- Fit standard wallboxes
- Break-off tabs on devices with AC quiet switches permit conversion to seperate feeds
- Backed by a Limited Two-Year Warranty

#### Color: Brown


Mechanical Specifications Termination: Side Terminal ID: Brass-Hot Black-Hot White-Neutral Green-Gnd Terminal Accom.: 14-12 AWG Product ID: Stamped on Strap Torque Range: 12-14 inch pounds

## Product Features

Voltage: 120 VAC Color: Brown Warranty: 2 Year Limited

Standards and Certifications NEMA: WD-1 & WD-6 ANSI: C-73 UL Standard: UL 20 CSA C22.2 No. 111: File #152105 NOM: 057 Warranty: 2 Year Limited

## **Dimensional Diagram**



## SPECIFICATION SUBMITTAL

JOB NAME:	CATALOG NUMBERS:	
JOB NUMBER:		

## Leviton Manufacturing Co., Inc.

201 North Service Road, Melville, NY 11747 Telephone: +1-800-323-8920 · FAX: +1-800-832-9538 · Tech Line (8:30AM-7:30PM E.S.T. Monday-Friday): +1-800-824-3005

## Leviton Manufacturing of Canada, Ltd.

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: +1-800-469-7890 · FAX: +1-800-824-3005 · www.leviton.com/canada

## Leviton S. de R.L. de C.V.

Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52)5386-1797 · www.leviton.com.mx

## Visit our Website at: www.leviton.com

© 2018 Leviton Manufacturing Co., Inc. All Rights Reserved. Subject to change without notice.

## Leviton has a global presence.

If you would like to know where your local Leviton office is located please go to: www.leviton.com/international/contacts/

