



# SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of:  
US OSHA Hazard Communication Standard (29 CFR 1910.1200)

Revision date 07-Jul-2025

Version 13

## 1. Identification

### Product identifier

**Product Name** WS Aged Oak

### Other means of identification

**Product Code(s)** 12604

**Synonyms** None

### Recommended use of the chemical and restrictions on use

**Recommended Use** No information available

**Restrictions on use** No information available

### Details of the supplier of the safety data sheet

#### Supplier Address

Old Masters  
303 19th St. SE  
Orange City, IA 51041  
Phone: 712-737-4993  
Fax: 712-737-4997

#### Manufacturer Address

Diamond Vogel  
1020 Albany Place SE  
Orange City, IA 51041  
Phone: (712) 737-4993  
Fax: (712) 737-4997

### Emergency telephone number

**Emergency Telephone** Chemtrec 1-800-424-9300

## 2. Hazard(s) identification

### Classification

Flammable liquids	Category 3
Skin sensitization	Category 1
Germ cell mutagenicity	Category 1B
Carcinogenicity	Category 1A
Reproductive toxicity	Category 1B
Specific target organ toxicity (repeated exposure)	Category 1
Aspiration hazard	Category 1

### Hazards not otherwise classified (HNOC)

Not applicable

### Label elements

**Danger****Hazard statements**

Flammable liquid and vapor.  
 May cause an allergic skin reaction.  
 May cause genetic defects.  
 May cause cancer.  
 May damage fertility or the unborn child.  
 Causes damage to organs through prolonged or repeated exposure.  
 May be fatal if swallowed and enters airways.

**Precautionary Statements - Prevention**

Obtain special instructions before use.  
 Do not handle until all safety precautions have been read and understood.  
 Wear protective gloves/protective clothing/eye protection/face protection.  
 Contaminated work clothing must not be allowed out of the workplace.  
 Do not breathe dust/fume/gas/mist/vapors/spray.  
 Wash face, hands and any exposed skin thoroughly after handling.  
 Do not eat, drink or smoke when using this product.  
 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
 Keep container tightly closed.  
 Ground/bond container and receiving equipment.  
 Use only non-sparking tools.  
 Take precautionary measures against static discharge.  
 Use explosion-proof electrical/ ventilating/ lighting/ equipment.

**Precautionary Statements - Response**

IF exposed or concerned: Get medical advice/attention.  
 If skin irritation or rash occurs: Get medical advice/attention.  
 Wash contaminated clothing before reuse.  
 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.  
 IF SWALLOWED: Immediately call a POISON CENTER or doctor.  
 Do NOT induce vomiting.  
 In case of fire: Use CO<sub>2</sub>, dry chemical, or foam to extinguish.

**Precautionary Statements - Storage**

Store locked up.  
 Store in a well-ventilated place. Keep cool.

**Precautionary Statements - Disposal**

Dispose of contents/container to an approved waste disposal plant.

**Other information**

No information available.

### 3. Composition/information on ingredients

**Substance**

Not applicable.

**Mixture**

Chemical name	CAS No.	Weight-%	Trade secret
---------------	---------	----------	--------------

Soybean oil	8001-22-7	20 to <35	*
Talc (powder)	14807-96-6	20 to <35	*
Solvent Naphtha, Medium Aliphatic	64742-88-7	10 to <20	*
Titanium dioxide	13463-67-7	5 to <10	*
Linseed Oil	8001-26-1	1 to <5	*
Zirconium octoate	22464-99-9	0.1 to <1	*
Mineral Spirits	64742-48-9	0.1 to <1	*
Cobalt 2-ethylhexanoate	136-52-7	0.1 to <1	*
Methyl Ethyl Ketoxime	96-29-7	0.1 to <1	*
Carbon Black	1333-86-4	0.1 to <1	*
Crystalline Silica	14808-60-7	0.1 to <1	*
Ethyl Benzene	100-41-4	0.1 to <1	*

\*The exact percentage (concentration) of composition has been withheld as a trade secret.

## 4. First-aid measures

### Description of first aid measures

<b>General advice</b>	Show this safety data sheet to the doctor in attendance. IF exposed or concerned: Get medical advice/attention. Immediate medical attention is required.
<b>Inhalation</b>	Aspiration into lungs can produce severe lung damage. If breathing has stopped, give artificial respiration. Get medical attention immediately. Remove to fresh air. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. If breathing is difficult, (trained personnel should) give oxygen. Get immediate medical attention. Delayed pulmonary edema may occur.
<b>Eye contact</b>	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Keep eye wide open while rinsing. Do not rub affected area.
<b>Skin contact</b>	Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. May cause an allergic skin reaction. In the case of skin irritation or allergic reactions see a physician.
<b>Ingestion</b>	ASPIRATION HAZARD IF SWALLOWED - CAN ENTER LUNGS AND CAUSE DAMAGE. Do NOT induce vomiting. If vomiting occurs spontaneously, keep head below hips to prevent aspiration. Rinse mouth. Never give anything by mouth to an unconscious person. Get immediate medical attention.
<b>Self-protection of the first aider</b>	Remove all sources of ignition. Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination. Use personal protective equipment as required. See section 8 for more information. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation.

### Most important symptoms and effects, both acute and delayed

<b>Symptoms</b>	Itching. Rashes. Hives. Difficulty in breathing. Coughing and/ or wheezing. Dizziness.
<b>Effects of Exposure</b>	May cause cancer. May cause adverse reproductive effects - such as birth defect, miscarriages, or infertility. Mutagenic effects. Causes damage to organs through prolonged or repeated exposure.

### Indication of any immediate medical attention and special treatment needed

<b>Note to physicians</b>	May cause sensitization in susceptible persons. Treat symptomatically. Because of the danger of aspiration, emesis or gastric lavage should not be employed unless the risk is justified by the presence of additional toxic substances.
---------------------------	--

## 5. Fire-fighting measures

<b>Suitable Extinguishing Media</b> Large Fire	Dry chemical. Carbon dioxide (CO <sub>2</sub> ). Water spray. Alcohol resistant foam. CAUTION: Use of water spray when fighting fire may be inefficient.
<b>Unsuitable extinguishing media</b>	Do not scatter spilled material with high pressure water streams.
<b>Specific hazards arising from the chemical</b>	Risk of ignition. Keep product and empty container away from heat and sources of ignition. In the event of fire, cool tanks with water spray. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. Product is or contains a sensitizer. May cause sensitization by skin contact. WARNING: Spontaneous combustion (fire) may result from materials such as rags, steel wool, paper, clothing, and other waste soaked in linseed oil. Place in a sealed, water filled, metal container to prevent this. WARNING: Spontaneous combustion (fire) may result from materials such as rags, steel wool, paper, clothing, and other waste soaked in soybean oil. Place in a sealed, water filled, metal container to prevent this.
<b>Explosion data</b>	
<b>Sensitivity to mechanical impact</b>	None.
<b>Sensitivity to static discharge</b>	Yes.
<b>Special protective equipment and precautions for fire-fighters</b>	Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protection equipment.

## 6. Accidental release measures

### Personal precautions, protective equipment and emergency procedures

<b>Personal precautions</b>	Evacuate personnel to safe areas. Use personal protective equipment as required. See section 8 for more information. Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Keep people away from and upwind of spill/leak. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Pay attention to flashback. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Do not touch or walk through spilled material.
<b>Other information</b>	Ventilate the area. Refer to protective measures listed in Sections 7 and 8.

### Methods and material for containment and cleaning up

<b>Methods for containment</b>	Stop leak if you can do it without risk. Do not touch or walk through spilled material. A vapor suppressing foam may be used to reduce vapors. Dike far ahead of spill to collect runoff water. Keep out of drains, sewers, ditches and waterways. Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal.
<b>Methods for cleaning up</b>	Take precautionary measures against static discharges. Dam up. Soak up with inert absorbent material. Pick up and transfer to properly labeled containers.

## 7. Handling and storage

### Precautions for safe handling

<b>Advice on safe handling</b>	Use personal protection equipment. Avoid breathing vapors or mists. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use grounding and bonding connection when transferring this material to prevent static discharge, fire or explosion. Use with local exhaust ventilation. Use spark-proof tools and explosion-proof equipment. Keep in an area equipped with sprinklers. Use according to package label instructions. Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. In case of insufficient ventilation, wear suitable respiratory equipment. Do not eat, drink or smoke when using this product. Take off
--------------------------------	--

contaminated clothing and wash before reuse. Remove contaminated clothing and shoes.

### Conditions for safe storage, including any incompatibilities

#### Storage Conditions

Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Keep in properly labeled containers. Do not store near combustible materials. Keep in an area equipped with sprinklers. Store in accordance with the particular national regulations. Store in accordance with local regulations. Store locked up. Keep out of the reach of children. Store away from other materials.

## 8. Exposure controls/personal protection

### Control Parameters

#### Exposure Limits

The following ingredients are the only ingredients of the product above the cut-off level (or level that contributes to the hazard classification of the mixture) which have an exposure limit applicable in the region for which this safety data sheet is intended or other recommended limit. At this time, the other relevant constituents have no known exposure limits from the sources listed here.

Chemical name	ACGIH TLV	OSHA PEL	NIOSH
Talc (powder) 14807-96-6	TWA: 2 mg/m <sup>3</sup> respirable particulate matter particulate matter containing no Asbestos and <1% Crystalline silica	TWA: 20 mppcf if 1% Quartz or more, use Quartz limit (vacated) TWA: 2 mg/m <sup>3</sup> respirable dust <1% Crystalline silica, containing no Asbestos TWA: 20 mppcf if 1% Quartz or more, use Quartz limit	IDLH: 1000 mg/m <sup>3</sup> TWA: 2 mg/m <sup>3</sup> containing no Asbestos and <1% Quartz respirable dust
Titanium dioxide 13463-67-7	TWA: 0.2 mg/m <sup>3</sup> nanoscale respirable particulate matter TWA: 2.5 mg/m <sup>3</sup> finescale respirable particulate matter	TWA: 15 mg/m <sup>3</sup> total dust TWA: 5 mg/m <sup>3</sup> respirable fraction	IDLH: 5000 mg/m <sup>3</sup> TWA: 2.4 mg/m <sup>3</sup> CIB 63 fine TWA: 0.3 mg/m <sup>3</sup> CIB 63 ultrafine, including engineered nanoscale
Zirconium octoate 22464-99-9	STEL: 10 mg/m <sup>3</sup> Zr TWA: 5 mg/m <sup>3</sup> Zr	TWA: 5 mg/m <sup>3</sup> Zr (vacated) TWA: 5 mg/m <sup>3</sup> Zr (vacated) STEL: 10 mg/m <sup>3</sup> Zr	IDLH: 25 mg/m <sup>3</sup> Zr TWA: 5 mg/m <sup>3</sup> except Zirconium tetrachloride Zr STEL: 10 mg/m <sup>3</sup> Zr
Carbon Black 1333-86-4	TWA: 3 mg/m <sup>3</sup> inhalable particulate matter	TWA: 3.5 mg/m <sup>3</sup> (vacated) TWA: 3.5 mg/m <sup>3</sup>	IDLH: 1750 mg/m <sup>3</sup> TWA: 3.5 mg/m <sup>3</sup> TWA: 0.1 mg/m <sup>3</sup> Carbon black in presence of Polycyclic aromatic hydrocarbons PAH
Crystalline Silica 14808-60-7	TWA: 0.025 mg/m <sup>3</sup> respirable particulate matter	TWA: 50 µg/m <sup>3</sup> TWA: 50 µg/m <sup>3</sup> excludes construction work, agricultural operations, and exposures that result from the processing of sorptive clays (vacated) TWA: 0.1 mg/m <sup>3</sup> respirable dust : (250)/(%SiO <sub>2</sub> + 5) mppcf TWA respirable fraction : (10)/(%SiO <sub>2</sub> + 2) mg/m <sup>3</sup> TWA respirable fraction	IDLH: 50 mg/m <sup>3</sup> respirable dust TWA: 0.05 mg/m <sup>3</sup> respirable dust
Ethyl Benzene 100-41-4	TWA: 20 ppm	TWA: 100 ppm TWA: 435 mg/m <sup>3</sup> (vacated) TWA: 100 ppm (vacated) TWA: 435 mg/m <sup>3</sup>	IDLH: 800 ppm TWA: 100 ppm TWA: 435 mg/m <sup>3</sup> STEL: 125 ppm

		(vacated) STEL: 125 ppm (vacated) STEL: 545 mg/m <sup>3</sup>	STEL: 545 mg/m <sup>3</sup>
--	--	--	-----------------------------

**Biological occupational exposure limits**

Chemical name	ACGIH
Ethyl Benzene 100-41-4	150 mg/g creatinine - urine (Sum of mandelic acid and phenylglyoxylic acid) - end of shift

**Appropriate engineering controls**

<b>Engineering controls</b>	Showers Eyewash stations Ventilation systems.
-----------------------------	---

**Individual protection measures, such as personal protective equipment**

<b>Eye/face protection</b>	Tight sealing safety goggles.
<b>Hand protection</b>	Wear suitable gloves. Impervious gloves.
<b>Skin and body protection</b>	Wear suitable protective clothing. Long sleeved clothing. Chemical resistant apron. Antistatic boots.
<b>Respiratory protection</b>	No protective equipment is needed under normal use conditions. If exposure limits are exceeded or irritation is experienced, ventilation and evacuation may be required.
<b>General hygiene considerations</b>	Do not eat, drink or smoke when using this product. Contaminated work clothing should not be allowed out of the workplace. Regular cleaning of equipment, work area and clothing is recommended. Wash hands before breaks and immediately after handling the product.

**9. Physical and chemical properties****Information on basic physical and chemical properties**

<b>Physical state</b>	Liquid
<b>Appearance</b>	No information available
<b>Color</b>	No information available
<b>Odor</b>	No information available
<b>Odor threshold</b>	No information available

<b>Property</b>	<b>Values</b>	<b>Remarks • Method</b>
<b>pH</b>	No data available	None known
<b>pH (as aqueous solution)</b>		None known
<b>Melting point / freezing point</b>	No data available	None known
<b>Initial boiling point and boiling range</b>	No data available	None known
<b>Flash point</b>	38 °C / 100 °F	
<b>Evaporation rate</b>	No data available	None known
<b>Flammability</b>	No data available	None known
<b>Flammability Limit in Air</b>		None known
<b>Upper flammability or explosive limits</b>	No data available	
<b>Lower flammability or explosive limits</b>	No data available	
<b>Vapor pressure</b>	No data available	None known
<b>Relative vapor density</b>	No data available	None known
<b>Relative density</b>	1.16	
<b>Water solubility</b>	No data available	None known
<b>Solubility(ies)</b>	No data available	None known
<b>Partition coefficient</b>	No data available	None known
<b>Autoignition temperature</b>	No data available	None known

<b>Decomposition temperature</b>		None known
<b>Kinematic viscosity</b>	No data available	None known
<b>Dynamic viscosity</b>	No data available	None known

**Other information**

<b>Explosive properties</b>	No information available
<b>Oxidizing properties</b>	No information available
<b>Softening point</b>	No information available
<b>Molecular weight</b>	No information available
<b>VOC content</b>	No information available
<b>Liquid Density</b>	9.67 lbs/gal
<b>Bulk density</b>	No information available
<b>Percent solids by weight</b>	80.3%
<b>Percent volatile by weight</b>	19.7%
<b>Percent solids by volume</b>	71.0%
<b>Actual VOC (lbs/gal)</b>	1.8
<b>Actual VOC (grams/liter)</b>	222
<b>EPA VOC (lbs/gal)</b>	1.9
<b>EPA VOC (grams/liter)</b>	223

**10. Stability and reactivity**

<b>Reactivity</b>	No information available.
<b>Chemical stability</b>	Stable under normal conditions.
<b>Possibility of hazardous reactions</b>	None under normal processing.
<b>Conditions to avoid</b>	Heat, flames and sparks.
<b>Incompatible materials</b>	None known based on information supplied.
<b>Hazardous decomposition products</b>	None known based on information supplied.

**11. Toxicological information****Information on likely routes of exposure****Product Information**

<b>Inhalation</b>	Specific test data for the substance or mixture is not available. Aspiration into lungs can produce severe lung damage. May cause pulmonary edema. Pulmonary edema can be fatal. May cause irritation of respiratory tract.
<b>Eye contact</b>	Specific test data for the substance or mixture is not available. May cause irritation.
<b>Skin contact</b>	May cause sensitization by skin contact. Specific test data for the substance or mixture is not available. Repeated or prolonged skin contact may cause allergic reactions with susceptible persons. (based on components). Repeated exposure may cause skin dryness or cracking.
<b>Ingestion</b>	Specific test data for the substance or mixture is not available. Potential for aspiration if swallowed. May cause lung damage if swallowed. Aspiration may cause pulmonary edema and pneumonitis. May be fatal if swallowed and enters airways.

**Symptoms related to the physical, chemical and toxicological characteristics**

**Symptoms** Itching. Rashes. Hives. Difficulty in breathing. Coughing and/ or wheezing. Dizziness.

**Acute toxicity****Numerical measures of toxicity**

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral)	9,960.20 mg/kg
ATEmix (dermal)	9,031.00 mg/kg
ATEmix (inhalation-dust/mist)	18.04 mg/l

#### Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Talc (powder) 14807-96-6	= 55,000 mg/kg (Rat)	-	-
Solvent Naphtha, Medium Aliphatic 64742-88-7	> 25 mL/kg ( Rat )	> 4000 mg/kg ( Rabbit )	> 5.28 mg/L ( Rat ) 4 h
Titanium dioxide 13463-67-7	> 2000 mg/kg ( Rat )	-	> 5.09 mg/L ( Rat ) 4 h
Linseed Oil 8001-26-1	> 15,000 mg/kg	-	-
Zirconium octoate 22464-99-9	> 5000 mg/kg (Rat)	-	-
Mineral Spirits 64742-48-9	> 6000 mg/kg ( Rat )	> 5000 mg/kg ( Rabbit )	> 8500 mg/m <sup>3</sup> ( Rat ) 4 h
Cobalt 2-ethylhexanoate 136-52-7	= 1300 mg/kg (Rat)	> 5000 mg/kg ( Rabbit )	> 10 mg/L ( Rat ) 1 h
Methyl Ethyl Ketoxime 96-29-7	= 930 mg/kg ( Rat )	1000 - 1800 mg/kg ( Rabbit )	> 4.83 mg/L ( Rat ) 4 h
Carbon Black 1333-86-4	> 10000 mg/kg ( Rat )	> 2000 mg/kg ( Rabbit )	> 4.6 mg/m <sup>3</sup> ( Rat ) 4 h
Crystalline Silica 14808-60-7	> 22,500 mg/kg (Rat)	-	-
Ethyl Benzene 100-41-4	= 3500 mg/kg ( Rat )	= 15400 mg/kg ( Rabbit )	= 17.4 mg/L ( Rat ) 4 h

#### Delayed and immediate effects as well as chronic effects from short and long-term exposure

**Skin corrosion/irritation** No information available.

**Serious eye damage/eye irritation** No information available.

**Respiratory or skin sensitization** May cause an allergic skin reaction.

**Germ cell mutagenicity** Contains a known or suspected mutagen. Classification based on data available for ingredients. May cause genetic defects.

**Carcinogenicity** Contains a known or suspected carcinogen. Classification based on data available for ingredients. May cause cancer.

The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical name	ACGIH	IARC	NTP	OSHA
Talc (powder) 14807-96-6	-	Group 2A	-	X
Titanium dioxide 13463-67-7	A3	Group 2B	-	X
Cobalt 2-ethylhexanoate 136-52-7	-	Group 2B Group 3	Reasonably Anticipated	X
Carbon Black 1333-86-4	A3	Group 2B	-	X
Crystalline Silica 14808-60-7	A2	Group 1	Known	X
Ethyl Benzene	A3	Group 2B	-	X

100-41-4				
----------	--	--	--	--

**Legend**

- ACGIH (American Conference of Governmental Industrial Hygienists)**
- A2 - Suspected Human Carcinogen
- A3 - Animal Carcinogen
- IARC (International Agency for Research on Cancer)**
- Group 1 - Carcinogenic to Humans
- Group 2A - Probably Carcinogenic to Humans
- Group 2B - Possibly Carcinogenic to Humans
- Group 3 - Not Classifiable as to Carcinogenicity in Humans
- NTP (National Toxicology Program)**
- Known - Known Carcinogen
- Reasonably Anticipated - Reasonably Anticipated to be a Human Carcinogen
- OSHA (Occupational Safety and Health Administration of the US Department of Labor)**
- X - Present

- Reproductive toxicity** Classification based on data available for ingredients. May damage fertility or the unborn child.
- STOT - single exposure** No information available.
- STOT - repeated exposure** Causes damage to organs through prolonged or repeated exposure.
- Target organ effects** Respiratory system, Eyes, Central Vascular System (CVS), Lungs.
- Aspiration hazard** May be fatal if swallowed and enters airways.
- Other adverse effects** No information available.
- Interactive effects** No information available.

**12. Ecological information**

**Ecotoxicity**

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea
Talc (powder) 14807-96-6	-	100: 96 h Brachydanio rerio g/L LC50 semi-static	-	-
Solvent Naphtha, Medium Aliphatic 64742-88-7	450: 96 h Pseudokirchneriella subcapitata mg/L EC50	800: 96 h Pimephales promelas mg/L LC50 static	-	100: 48 h Daphnia magna mg/L EC50
Mineral Spirits 64742-48-9	-	2200: 96 h Pimephales promelas mg/L LC50	-	-
Methyl Ethyl Ketoxime 96-29-7	83: 72 h Desmodesmus subspicatus mg/L EC50	777 - 914: 96 h Pimephales promelas mg/L LC50 flow-through 760: 96 h Poecilia reticulata mg/L LC50 static	-	750: 48 h Daphnia magna mg/L EC50
Ethyl Benzene 100-41-4	4.6: 72 h Pseudokirchneriella subcapitata mg/L EC50	11.0 - 18.0: 96 h Oncorhynchus mykiss mg/L LC50 static	-	1.8 - 2.4: 48 h Daphnia magna mg/L EC50

	438: 96 h Pseudokirchneriella subcapitata mg/L EC50 2.6 - 11.3: 72 h Pseudokirchneriella subcapitata mg/L EC50 static 1.7 - 7.6: 96 h Pseudokirchneriella subcapitata mg/L EC50 static	4.2: 96 h Oncorhynchus mykiss mg/L LC50 semi-static 7.55 - 11: 96 h Pimephales promelas mg/L LC50 flow-through 32: 96 h Lepomis macrochirus mg/L LC50 static 9.1 - 15.6: 96 h Pimephales promelas mg/L LC50 static 9.6: 96 h Poecilia reticulata mg/L LC50 static		
--	--	---	--	--

**Persistence and degradability** No information available.

**Bioaccumulation**

**Component Information**

Chemical name	Partition coefficient
Methyl Ethyl Ketoxime 96-29-7	0.65
Ethyl Benzene 100-41-4	3.6

**Other adverse effects** No information available.

**13. Disposal considerations**

**Disposal methods**

**Waste from residues/unused products** Should not be released into the environment. Dispose of in accordance with local regulations. Dispose of waste in accordance with environmental legislation.

**Contaminated packaging** Empty containers pose a potential fire and explosion hazard. Do not cut, puncture or weld containers.

**California Hazardous Waste Status** This product contains one or more substances that are listed with the State of California as a hazardous waste.

**14. Transport information**

**DOT** Not regulated

**TDG** Not regulated

**MEX** Not regulated

**ICAO (air)** Not regulated

**IATA** Not regulated

**IMDG** Not regulated

**15. Regulatory information**

**International Inventories**

**TSCA** Complies

\*Contact supplier for details. One or more substances in this product are either not listed on the US TSCA inventory, listed on the confidential US TSCA inventory or are otherwise exempted from inventory listing requirements

**DSL/NDSL** Complies  
**EINECS/ELINCS** Contact supplier for inventory compliance status.  
**ENCS** Contact supplier for inventory compliance status.  
**IECSC** .  
**KECL** Contact supplier for inventory compliance status.  
**PICCS** Contact supplier for inventory compliance status.  
**AIC** Contact supplier for inventory compliance status.  
**NZIoC** Contact supplier for inventory compliance status.

**Legend:**

**TSCA** - United States Toxic Substances Control Act Section 8(b) Inventory  
**DSL/NDSL** - Canadian Domestic Substances List/Non-Domestic Substances List  
**EINECS/ELINCS** - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances  
**ENCS** - Japan Existing and New Chemical Substances  
**IECSC** - China Inventory of Existing Chemical Substances  
**KECL** - Korean Existing and Evaluated Chemical Substances  
**PICCS** - Philippines Inventory of Chemicals and Chemical Substances  
**AICS** - Australian Inventory of Chemical Substances  
**NZIoC** - New Zealand Inventory of Chemicals

**US Federal Regulations****SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

Chemical name	SARA 313 - Threshold Values %
Cobalt 2-ethylhexanoate - 136-52-7	0.1
Ethyl Benzene - 100-41-4	0.1

**SARA 311/312 Hazard Categories**

Should this product meet EPCRA 311/312 Tier reporting criteria at 40 CFR 370, refer to Section 2 of this SDS for appropriate classifications.

**CWA (Clean Water Act)**

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42).

Chemical name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Ethyl Benzene 100-41-4	1000 lb	X	X	X

**CERCLA**

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302).

Chemical name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	Reportable Quantity (RQ)
Ethyl Benzene 100-41-4	1000 lb	-	RQ 1000 lb final RQ RQ 454 kg final RQ

**US State Regulations**

**California Proposition 65**

This product contains the following Proposition 65 chemicals:

Chemical name	California Proposition 65
Titanium dioxide - 13463-67-7	Carcinogen
Carbon Black - 1333-86-4	Carcinogen
Crystalline Silica - 14808-60-7	Carcinogen
Ethyl Benzene - 100-41-4	Carcinogen
Naphthalene - 91-20-3	Carcinogen
Lead - 7439-92-1	Carcinogen Developmental Female Reproductive Male Reproductive
Toluene - 108-88-3	Developmental
Benzene(including benzene from gasoline) - 71-43-2	Carcinogen Developmental Male Reproductive
Cumene - 98-82-8	Carcinogen
Propylene oxide - 75-56-9	Carcinogen
Mercury - 7439-97-6	Developmental
Nickel - 7440-02-0	Carcinogen
Cadmium - 7440-43-9	Carcinogen Developmental Male Reproductive

**U.S. State Right-to-Know Regulations**

Chemical name	New Jersey	Massachusetts	Pennsylvania
Soybean oil 8001-22-7	-	-	X
Talc (powder) 14807-96-6	X	X	X
Titanium dioxide 13463-67-7	X	X	X
Linseed Oil 8001-26-1	-	-	X
Xylene 1330-20-7	X	X	X
1,2,4-Trimethylbenzene 95-63-6	X	X	X
Cobalt 2-ethylhexanoate 136-52-7	X	-	X
Iron (III) oxide, as Fe 1309-37-1	X	-	X
Silica, Amorphous fumed 7631-86-9	-	X	X
Magnesium carbonate 546-93-0	X	X	-
Carbon Black 1333-86-4	X	X	X
Crystalline Silica 14808-60-7	X	X	X
Ethyl Benzene 100-41-4	X	X	X
Propylene Glycol Methyl Ether 107-98-2	X	X	X
Diethylene Glycol Methyl Ether 111-77-3	X	X	X
Nonane 111-84-2	X	X	X
Stoddard Solvent	X	X	X

8052-41-3			
Diethylene Glycol Butyl Ether 112-34-5	X	-	X
Propionic Acid 79-09-4	X	X	X
2-Ethylhexanoic acid 149-57-5	X	-	-
Barium sulfate 7727-43-7	X	X	X
Naphthalene 91-20-3	X	X	X
Lead 7439-92-1	X	X	X
Benzene(including benzene from gasoline) 71-43-2	X	X	X
Toluene 108-88-3	X	X	X
Cumene 98-82-8	X	X	X
Propylene oxide 75-56-9	X	X	X
Mercury 7439-97-6	X	X	X
Nickel 7440-02-0	X	X	X
Arsenic 7440-38-2	X	X	X
Cadmium 7440-43-9	X	X	X

**U.S. EPA Label Information**

EPA Pesticide Registration Number Not applicable

LIST OF HAZARDOUS AIR POLLUTANTS SUBJECT TO THE PROVISIONS OF THE CLEAN AIR ACT, TITLE I SECTION 112 'National Emission Standards for Hazardous Air Pollutants' (present if listed in Section 3):

Chemical name	Weight % of HAPS in Product	Pounds HAPS / Gal Product
Cobalt 2-ethylhexanoate 136-52-7	0.46	0.04
Ethyl Benzene 100-41-4	0.13	0.01

**16. Other information****Key or legend to abbreviations and acronyms used in the safety data sheet****Legend Section 8: Exposure controls/personal protection**

TWA	TWA (time-weighted average)	STEL	STEL (Short Term Exposure Limit)
Ceiling	Maximum limit value	*	Skin designation
+	Sensitizers		

**Key literature references and sources for data used to compile the SDS**

Agency for Toxic Substances and Disease Registry (ATSDR)  
U.S. Environmental Protection Agency ChemView Database  
European Food Safety Authority (EFSA)  
Environmental Protection Agency  
Acute Exposure Guideline Level(s) (AELG(s))  
U.S. Environmental Protection Agency Federal Insecticide, Fungicide, and Rodenticide Act  
U.S. Environmental Protection Agency High Production Volume Chemicals  
Food Research Journal  
Hazardous Substance Database  
International Uniform Chemical Information Database (IUCLID)

National Institute of Technology and Evaluation (NITE)  
Australia National Industrial Chemicals Notification and Assessment Scheme (NICNAS)  
NIOSH (National Institute for Occupational Safety and Health)  
National Library of Medicine's ChemID Plus (NLM CIP)  
National Library of Medicine's PubMed database (NLM PUBMED)  
U.S. National Toxicology Program (NTP)  
New Zealand's Chemical Classification and Information Database (CCID)  
Organization for Economic Co-operation and Development Environment, Health, and Safety Publications  
Organization for Economic Co-operation and Development High Production Volume Chemicals Program  
Organization for Economic Co-operation and Development Screening Information Data Set  
World Health Organization

**Revision date** 07-Jul-2025  
**Revision Note** No information available.

**Disclaimer**

**The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.**

**End of Safety Data Sheet**