

NEW ITEMS

ProLineTM
SERIES

2024 NEW SKUS RECAP

07/29/2024

CONNECT
WITH QUALITY

F1960 PEX SUPPLY STOPS

Features, Applications, Certifications, & Availability



FEATURES & APPLICATIONS

- F1960 Expansion PEX fittings for use with PEX-A Tubing
- Chrome Plated finish on body for additional corrosion resistance
- Oval quarter-turn handle for easy on/off operation
- Approved for indoor or outdoor use
- Lead Free
- Maximum Pressure: 125 PSI
- Temperature Range: 40°F to 160°F
- Double O-Ring on stem for safety

APPLICABLE CERTIFICATIONS



Item #	Size	Connection Type	Valve Type
190-862HC	1/2-in x 3/8-in	F1960 PEX x COMP	Angle
191-862HC	1/2-in x 3/8-in	F1960 PEX x COMP	Straight

Links for more information:
[List Price Sheet: SS_0622](#)
[Product Listings](#)

PEX TANKLESS WATER HEATER VALVE KIT

Features, Applications, & Certifications

FEATURES & APPLICATIONS

- Lead-free forged brass construction supports a durable long-lived product
- Hot (red) and cold (blue) water valve handles are color coded for easy visual identification
- Includes pressure relief valve (PRV) with stainless steel handle for quick & easy operations
- 200,000 BTU / hour rating on pressure relief valve
- Designed with full ports to minimize turbulence
- Temperature Range: 32° to 180°F
- Maximum Pressure: 600 PSI (Hot & Cold valves)
- Working Pressure: 150 PSI (PRV)
- 3/4-in NPT thread connections
- Rubber connectors prevent caps from being lost during maintenance
- Compatible with most Tankless Water Heaters



PEX F1960 KIT

- 102-140 (Expansion PEX)
- Valve Kit includes:
 - ✓ One hot water valve
 - ✓ One cold water valve
 - ✓ One pressure relief valve

APPLICABLE CERTIFICATIONS FOR PRV



PEX F1807 KIT

- 102-130 (CRIMP PEX)
- Valve Kit includes:
 - ✓ One hot water valve
 - ✓ One cold water valve
 - ✓ One pressure relief valve

ProLine™
SERIES

Links for more information:
[List Price Sheet: VLV_0624](#)
[Product Listings](#)

STAINLESS STEEL BALL VALVES

Features, Applications, & Availability



FEATURES & APPLICATIONS

- Made of durable 304 stainless steel
- Full port for maximum flow rate
- Maximum Pressure: 1000 psi
- Working Pressure: 600 psi
- Temperature Range: -4°F to 392°F
- Packing gland – blowout proof stem design
- Handle has simple locking mechanism for flow control
- Quarter-turn lever handle for easy “On/Off” operation
- Perfect for areas where high corrosion resistance is required.

Item #	Size	Connection Type
107-711SS	1/4-in	FIP x FIP
107-712SS	3/8-in	FIP x FIP
107-713SS	1/2-in	FIP x FIP
107-714SS	3/4-in	FIP x FIP
107-715SS	1-in	FIP x FIP
107-716SS	1-1/4-in	FIP x FIP
107-717SS	1-1/2-in	FIP x FIP
107-718SS	2-in	FIP x FIP

Links for more information:
[List Price Sheet: VLV_0624](#)
[Product Listings](#)