



RUST-OLEUM® SURE COLOR® INTERIOR PAINT + PRIMER

DESCRIPTION AND USES

Rust-Oleum® Sure Color® Interior Wall Paint is a ready-to-use formula that provides the right color every time. This paint and primer in one delivers excellent coverage with a durable finish that is highly washable and scrubbable. A convenient solution that is ideal for interior walls, trim, windows and doors.

PRODUCTS

DESCRIPTION (Gallon)	SKU
Flat White	380215
Flat Black	380216
Eggshell White	380217
Eggshell Black	380218
Eggshell Alpine White	380219
Eggshell Linen White	380220
Eggshell Antique White	380221
Eggshell Soft Beige	380222
Eggshell Dove Gray	380223
Eggshell Store Gray	380224
Eggshell Sky Blue	380225
Eggshell Smoked Navy	380226
Semi-Gloss White	380227
Semi-Gloss Black	380228

PRODUCT APPLICATION

READ ALL DIRECTIONS BEFORE BEGINNING PROJECT

SURFACE PREPARATION

Surface must be free of any dust, grease, oil, stains, rust or any other contaminants. Sand glossy surfaces before painting and wash walls if necessary. Fill in any cracks or holes to ensure a smooth surface. Drywall joint compound must dry for two days. New drywall and bare wood should be primed before painting. Allow new plaster to cure for 30 days before painting. We recommend the use of Zinsser Bulls Eye 1-2-3® Primer to protect new drywall, painting over contrasting colors, bare woods and metals or where paint adhesion could propose a problem.

WARNING: If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

PRODUCT APPLICATION (cont.)

COVERAGE/WHERE TO USE

One gallon will cover up to 400 sq. ft., depending on surface texture, porosity, and application method. Dark colors may require multiple coats. Ideal for interior walls, trim, windows, and doors. Surfaces - Drywall, masonry and wood.

NOTE: Not recommended for use on floors or exterior surfaces.

APPLICATION

Stir well before use. Inter mix cans of the same color and product to ensure color consistency. Apply using a high quality 3/8"-1/2" nap roller or a high quality brush. If using an airless sprayer, follow manufacturer's instructions for use, and use a .015"-.021" tip at 1800-2300 psi, adjusting as needed. Apply using even strokes, moving from dry to wet areas, keeping a wet edge. Two coats are required for new or uncoated surfaces. Some colors may require additional coats. Thinning is not recommended.

DRY AND RECOAT TIMES

Based on 77°F (25°C) <50% humidity, dries to the touch in one hour. May be recoated after four hours. Allow more time to dry at cooler temperatures or in high humidity.

CLEAN-UP

Clean hands, tools, spills and splatters with soap and warm water.

DISPOSAL

To dispose of empty containers and unused product, contact your local environmental regulatory agency.

MAINTENANCE CARE

Do not place objects on painted surfaces until thoroughly dry. Freshly painted surfaces may be washed after 30 days. Clean with mild, non-oily soap and water.

NO TINTING REQUIRED.

PROTECT FROM FREEZING.

	TECHNICAL DATA	ROC-243
• TRUSTED QUALITY SINCE 1921 • 	RUST-OLEUM® SURE COLOR® INTERIOR PAINT + PRIMER	

PHYSICAL PROPERTIES

		SURE COLOR INTERIOR PAINT + PRIMER
Resin Type		Styrene Acrylic
Pigment Type		Varies by color
Solvents		Water, Glycol Ethers
Weight	Per Gallon	10.0-11.25 lbs.
	Per Liter	1.22-1.35 kg
Solids	By Weight	40-50%
	By Volume	30-35%
Volatile Organic Compounds		<50 g/l (lbs./gal.)
Recommended Dry Film Thickness (DFT) per Coat		1.5-2.0 mils (37.5-50µ)
Wet Film to Achieve DFT (unthinned material)		2.5-5.5 mils (62.5-137.5µ)
Practical Coverage at Recommended DFT (assumes 15% material loss)		Gallon up to 400 sq. ft. Depending on application method and surface porosity
Dry Times at 77°F (25°C) and 50% Relative Humidity	Touch	1 hour
	Recoat	4 hours
	Full Cure	7-10 days
Shelf Life		3 years
Flash Point		>200°F (93°C)
Storage		PROTECT FROM FREEZING
Safety Information		For additional information, see SDS

Calculated values are shown and may vary from the actual manufactured material.

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.