



Valspar® Porch, Floor And Patio Paint – Latex Satin

No. 49816 Series

GENERAL DESCRIPTION

Valspar® Porch, Floor And Patio Paint is a satin sheen coating that gives floors tough, long-lasting protection. The premium quality, polyurethane fortified acrylic latex formula is ideal for indoor applications where fast dry is important. Fast and easy water cleanup. This weather resistant formula can be used indoors or out and gives years of long lasting beauty and protection.

PRODUCT FEATURES

- Use on wood, concrete, floors, primed metal, steps, railings and porches
- Polyurethane fortified - Increases weather resistance and peel resistance
- Weather resistant
- For interior and exterior use

RECOMMENDED USES

- Concrete
- Wood
- Primed metal
- Porches
- Basement floors
- Stairs
- Breezeways
- Indoor and outdoor floors

Not for use on exterior wood decks, garage floors, or other automobile parking areas

SHIPPING AND PACKAGING

Freight Classification: Paint or paint related material. Protect from freezing.

Packaging:

Quart - - 4 per carton
Gallon - 4 per carton

COMPOSITION

Base and Fill Levels

(oz./gal.)

White (49816)	128
Light Gray (65735)	128
Dark Gray (65737)	128
Brick Red (67000)	128
Brownstone (67235)	128
Base 2 (49817)	124
Base 4 (49818)	116

APPLICATION AND CLEANUP

Stir thoroughly before and during use. Intermix all cans of the same color. To increase traction, add an anti-skid additive when applying the finishing coat. Use a premium-quality roller, polyester brush, pad applicator or airless sprayer. DO NOT USE ANTI-SKID ADDITIVE OR SAND IF SPRAYING. Apply liberally over the full length of the surface to avoid lap marks. If applied by airless sprayer, back-roll to ensure proper penetration. Finish with long, even strokes in one direction. Do not allow water to pond or puddle on newly painted surfaces. Clean tools and hands with warm, soapy water.

Airless Spray:

Pressure: 2000 PSI
Tip: 0.017–0.019”

Brush: Premium-quality polyester

Roller: Premium-quality roller 3/8" nap

Thinning: Thinning is not recommended. For surfaces that require 2 coats, such as new concrete or badly worn areas, thin the first coat with 16 oz. water per gallon (473 mL per 3.78 L).

SYSTEM

RECOMMENDATIONS

Properly Prepared Concrete:

1-2 Coats: Valspar Porch & Floor Latex Satin Enamel

Wood:

1 Coat: Valspar® Exterior Latex
1-2 Coats: Valspar Porch & Floor Latex Satin Enamel

Metal:

1 Coat: Valspar® Armor Anti-Rust Primer (21852)
1-2 Coats: Valspar Porch & Floor Latex Satin Enamel

Previously Painted Surfaces:

1-2 Coats: Valspar Porch & Floor Latex Satin Enamel

PRODUCT SPECIFICATIONS

Vehicle Type: Acrylic resin

Pigment type: Titanium dioxide

Viscosity: 86–94 Krebs Units

Gloss: 5-15 @ 60° angle

Flashpoint: N/A

VOC (g/L): less than 50 g/L 0.42 lb/gal as per 40 CFR 59.406

VOC (lbs./gal.): 31 ±2%

Volume Solids: 44% ±2%

Weight Solids: 36%

Weight Per Gallon: 10.28 ± .2 lbs./gal.

Practical Coverage:

One gallon (3.78 L) covers up to 400 sq. ft. (37 m²), depending upon surface porosity.

Recommended Film Thickness:

4.0 mil Wet 1.2 mil Dry

Dry Time @ 77 °F and 50% Relative Humidity

Recoat: 24 hours

Light Foot Traffic: 24 hours

Normal Use: 72 hours for normal use

Application Temperature: 50–90 °F (10–32 °C)

Storage Temperature: 40–90°F (5–32°C)

REGULATORY COMPLIANCE

Current as of: 11/6/2017

SCAQMD	Yes
CARB 2000 SCM	Yes
CARB 2007 SCM	Yes
OTC/LADCO	Yes
US National	Yes

STORAGE AND DISPOSAL

Do not freeze. Keep container closed when not in use. Do not transfer contents to other containers for storage or disposal. In case of spillage, absorb with inert material such as sand or kitty litter. Dispose of contaminated absorbent, container and/or unused contents in accordance with local, state and federal regulations.

The data on this sheet represent typical values. Since application variables are a major factor in product performance, this information should serve only as a general guide. Valspar assumes no obligation or liability for use of this information. UNLESS VALSPAR AGREES OTHERWISE IN WRITING, VALSPAR MAKES NO WARRANTIES, EXPRESS OR IMPLIED, AND DISCLAIMS ALL IMPLIED WARRANTIES INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE OR FREEDOM FROM PATENT INFRINGEMENT. VALSPAR WILL NOT BE LIABLE FOR ANY SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES. Your only remedy for any defect in this product is the replacement of the defective product, or a refund of its purchase price, at our option.



Valspar® Porch, Floor And Patio Paint – Latex Satin

No. 49816 Series

SURFACE PREPARATION

General:

Read the Lead Warning paragraph. The surface must be clean, dry and free of all loose or peeling paint. Thoroughly clean surface and remove wax and grease with an all-purpose cleaner (TSP or substitute). Remove gloss from previously painted surfaces by sanding.

Wood:

Rough or repaired wood surfaces should be sanded smooth. Prime bare, new wood with Valspar® Exterior Latex Primer (165219). Prime badly worn spots on old wood with a thinned first coat of Valspar® Latex Porch & Floor Paint.

Concrete:

Allow surface to cure at least 60 days before painting. New, unpainted or smooth-worn concrete must be etched with a concrete cleaner, degreaser and etcher for proper penetration and adhesion. Follow all label instructions. After cleaning, degreasing and etching, apply 2 coats of Latex Porch & Floor Paint — the first coat thinned with 1 pint of water per gallon (473 mL per 3.78 L) of paint and the second coat as normal.

Etching instructions:

New, unpainted or smooth-worn concrete must be etched with a muriatic-acid solution for proper penetration and adhesion. Before preparing acid solution, READ ALL CAUTIONS AND WARNINGS on acid packaging. Wear appropriate protective clothing, goggles and rubber gloves when handling acid. Mix 1 quart of muriatic acid with 1 gallon of water. Flush floor with acid solution. DO NOT BREATHE VAPORS and make certain there is good ventilation. After 30 minutes or when acid solution stops bubbling, rinse with water while scrubbing floor with stiff broom to remove all powdery residue. Allow to dry.

Metal:

Remove rust and prime all iron and steel with Valspar® Armor Anti-Rust Primer (21852).

LEAD WARNING

WARNING! If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

LIMITED WARRANTY

This product is warranted for your complete satisfaction for as long as you reside in your home. This warranty covers product that is applied to a properly prepared residential surface in accordance with label directions and excludes product failure due to deterioration of the underlying surface, structural defects or failure of previous product. If the product fails to perform to your satisfaction, return any unused portion to the store with proof-of-purchase and you will receive, as your sole remedy under this warranty, your choice of additional product of equal value or a full refund. THIS WARRANTY EXCLUDES LABOR OR THE COST OF LABOR FOR THE APPLICATION OF ANY PRODUCT AND EXCLUDES ANY INCIDENTAL OR CONSEQUENTIAL DAMAGES. Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitations or exclusions may not apply to you. This warranty gives you specific rights, and you may also have other rights which vary from state to state.

CAUTIONS

WARNING! Contains Crystalline Silica. **KEEP OUT OF THE REACH OF CHILDREN.** May cause eye and skin irritation. USE ONLY WITH ADEQUATE VENTILATION. Avoid breathing vapors, spray mist or sanding dust. If painting indoors, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness, or if air monitoring demonstrates vapor/mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH approved) during and after application. Follow respirator manufacturer's directions for respirator use. When sanding, wear a dust mask. AVOID CONTACT WITH THE EYES AND SKIN. Wash thoroughly after use. Close container after each use. DO NOT TAKE INTERNALLY. Delayed effect from long-term exposure: Cancer Hazard. Contains crystalline silica, which can cause cancer. Risk depends upon duration and level of exposure to dust generated from sanding surfaces or spray mist. WARNING: This product contains a chemical known to the State of California to cause cancer. FIRST AID: EYE CONTACT: Flush thoroughly with water for at least 15 minutes. If irritation persists, get medical attention.* IF INHALED: If affected by vapor or spray mist, move to fresh air. If breathing difficulty continues, get medical attention.* IF SWALLOWED: Drink 2 glasses of water. Get medical attention immediately.*

*Call poison control center, hospital emergency room or physician immediately.

CL 3.3

For additional safety and chronic health hazard information, refer to the Material Safety Data Sheet for this product.

**EMERGENCY MEDICAL TELEPHONE:
1-888-345-5732**

Valspar, Cleveland, Ohio 44115
valsparpaint.com